





































مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 PSD81602-A360	8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call
2 PSD8802-A180	4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call
3 PFW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/2 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+		Call
p PFW8601-A180	3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832, 3.6mm fixed lens, Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+		Call
5 PDBW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+		Call
6 ITC237-PW1B-IRZ	دوربین ANPR با قابلیت تشخیص پلاک مناسب برای ورودی های پارکینگ 2 Megapixel Full HD WDR Access ANPR Camera -Embedded with LPR algorithm inside the camera -plate cutout, snapshot preview, recording -White list database,1 ch relay out to control the barrier performance for outdoor applications- 1/2.8" 2Megapixel progressive scan CMOS H.265/H.264M/H.264H/H.264B dual-stream encoding 25/30fps@1080P(1920x1080), 2.7mm~12mm Motorize lens WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC Mirco SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE		121,720,000
7 IPC5831EP-ZE	1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840x2160),25/30fps@3Mp(2304x1296) 2.7mm ~12mm motorized lens, Max. Aperture F1.6 WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB, 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs Length 50m , Smart IR, IP67,IK10, PoE (Tripwire Intrusion Object Abandoned/Missing Face)		89,000,000
8 HFW4831EP-SE	1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265+&H.265&H.264&MJPEG triple-stream encoding 15fps@4K(3840x2160),25/30fps@3Mp(2304x1296) Minimum Illumination 0.06Lux/F1.6( Color,1/3s,30IRE)/0.3Lux/F1.6( Color,1/30s,30IRE)/0Lux/F1.6(IR on) WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Roi 4mm & 2.8mm fixed lens, Max. IR LEDs Length 40m Face Detection, Tripwire, Intrusion, Object Abandoned / Missing Micro SD card memory , 128 GB, IP67, PoE Smart Detection (Tripwire Intrusion   Scene Change   Face)		53,000,000





ردیف	مشخصات فنی	تصویر	قیمت (ریال)
9	<p><b>NEW</b></p> <p>8MP Lite IR Vari-focal Bullet Network Camera  8MP, 1/2.7" Progressive CMOS  low illuminance 0.008 Lux@F1.5  high image definition 8MP@15fps &amp; 4MP@25/30fps  2.7-13.5mm Motorized Lens  SMART H.264+/H.265+, (MJPEG in Sub Stream)  IVS Intrusion, Tripwire  Micro SD 256GB, 1ch Audio I/O, 1ch Alarm I/O  WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch  12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p>		61,500,000
10	<p>8MP Lite IR Vari-focal Starlight Bullet Network Camera  1/2.7" progressive scan CMOS image sensor, low illuminance, high image definition  Smart H.265/H.264 codec, MJPEG, high compression rate, ultra-low bit rate  8MP (3840 × 2160) @15 fps, 2688×1520 @25/30 fps  WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Region of Interest, Voltage Detection  2.7 mm~13.5 mm Motorized fixed lens  Max. IR LEDs Length 60m, Micro SD card memory , 256 GB  IP67, PoE, Smart Detection (Tripwire Intrusion)</p>		60,000,000
11	<p>6MP WDR IR Bullet Network Camera  1/2.9" 6Megapixel progressive scan STARVIS™ CMOS  H.265&amp;H.264 Triple-stream encoding  20fps@6M(3072×2048),25/30fps@4M(2688×1520)  WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC  7mm~35mm(5x zoom) Motorized lens  Max. IR LEDs Length 100m, Micro SD card memory , 128 GB  2/1 Alarm in/out, 1/1 audio in/out, IP67, IK10, PoE  (Tripwire Intrusion   Object Abandoned   Missing  Face)</p>		89,000,000
12	<p>1/2.9" 6Megapixel progressive scan STARVIS™ CMOS  H. 265+ &amp; H.265 &amp; H.264+ &amp; H.264 triple-stream encoding  20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520)  WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC  3.6mm fixed lens, Max. IR LEDs Length 40m  Micro SD card memory , 128 GB, IP67, PoE  (Tripwire Intrusion  Object Abandoned/Missing  Face)</p>		44,000,000
13	<p>1/2.7" 5Megapixel progressive CMOS  2.7~13.5mm Motorized lens  15fps@5M(2592×1944)&amp;25/30fps@3M(2304×1296)  H.265+/H.265/H.264+/H.264 dual-stream encoding  WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC  Micro SD card 128GB, Max IR LEDs Length 60m ,Smart IR  IP67, PoE, Smart Detection (Tripwire Intrusion)</p>		53,500,000
14	<p>4MP Pro AI IR Vari-focal, WizMind 1/1.8" 4Megapixel progressive scan CMOS  H.265,H.264,H.264B,H.264H, MJPEG triple-stream encoding  Max 25/30fps@4Mp(2688×1520), 50/60fps@2Mp(1920 × 1080)  WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lens,  Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB  Audio In/Out 1/1, Alarm In/Out 2/1  Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving,  loitering detection, parking detection and people gathering  Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas  independent detection, Scene Change, Heatmap, IP67, IK10, PoE</p>		93,000,000
15	<p>4MP WDR IR Bullet Network Camera  1/3" 4Megapixel progressive scan CMOS  H.265+/H.265/H.264+/H.264 triple-stream encoding  Max 25/30fps@4Mp(2688×1520)  WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC,  2.7mm ~13.5mm motorized lens  Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB  Audio In/Out 1/1, Alarm In/Out 2/1  IP67, IK10, PoE, (Tripwire Intrusion   Object Abandoned / Missing   Face)</p>		75,000,000
16	<p><b>NEW</b></p> <p>2MP IR Vari-focal Bullet WizMind Network Camera  2MP 1/2.8" Progressive STARVIS™ CMOS  low illuminance 0.0015 Lux@F1.3  high image definition 2MP@25/30fps  7-35mm Motorized Lens  SMART H.264+/H.265+  IVS: Tripwire; intrusion; fast moving (with accurate classification of vehicle and human); loitering detection; people  gathering; parking detection  Face Detection with Face Attributes and Face Expression  People Counting with Queue Management  Micro SD card 256 GB, 1ch Audio I/O, 2/1 Alarm I/O  WDR (120db), EIS, Defog, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch  12V, PoE, IP67, IK10, 4 IR LEDs 120m Distance, Onvif Profile S/G/T</p>		77,000,000
17	<p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS  H.265+/H.265/H.264+/H.264 triple-stream encoding  50/60fps@1080(1920×1080)  WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC  5.3mm ~ 64mm 12x zoom lens  1/1 Audio in/Out, 2/1 Alarm In/Out  Micro SD card up to 128 GB, Max. IR LEDs Length 200m , Smart IR  IP67, IK10, PoE, (Tripwire Intrusion Object Abandoned/Missing Face)</p>		77,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
18	HFWS231EP-ZE	<p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 &amp; MJPEG triple-stream encoding 50/60fps@1080(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 13.5mm motorized lens 1/1 Audio in/Out, 2/1 Alarm In/Out Micro SD card memory , 128 GB, Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE, Smart Detection (Tripwire Intrusion Object Abandoned/Missing Face)</p>		72,000,000
19	DH-IPC-HFW4431EP-Z-S4	<p>4MP WDR IR Bullet Network Camera 1/3" 4Megapixel progressive CMOS 2.7mm~13.5mm motorized lens 25/30fps@4Mp(2688×1520) H.265&amp;H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Facedetection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 2/1 Alarm in/out, 1/1 audio in/out Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, IK10, PoE</p>		65,000,000
20	DH-IPC-HFW4431TP-S-S4	<p>4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688×1520) H.265&amp;H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>		34,500,000
21	HFWS3441TP-ZS-27135	<p>4MP IR Vari-focal Bullet WizSense Network Camera 1/3"4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.5 2.7 mm~13.5 mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>		57,000,000
22	IPC-HFW24395P-SA-LED	<p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>		28,200,000
23	HFWS2431TP-ZS-S2	<p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5, 2.7~13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance:60 m, Smart IR, IP67, PoE</p>		49,900,000
24	IPC-HFW1431S1-S4-S5	<p>4MP Entry IR Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.03 Lux @ F2.0 high image definition 4MP@25/30fps 3.6mm fixed lens, Smart H.265+/H.264+ WDR(120db), Roi, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, 1 IR LEDs 30m Distance, ONVIF (Profile S/Profile G/Profile T)</p>		21,000,000
25	HFWS1431SP-0360B-S4	<p>4MP Entry IR Fixed-focal Bullet Network Camera 1/3"4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.03 Lux@F2.0, 3.6 Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR, IP67, PoE</p>		22,800,000
26	IPC-HFW3541T-ZS	<p>5MP IR Vari-focal Bullet WizSense Network Camera 5MP, 1/2.7" Progressive CMOS 0.005 Lux@F1.5 (Color, 30IRE), 0.0005 Lux@F1.5 (B/W, 30IRE), 0 Lux (Illuminator on) high image definition 5MP@20fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+ 3 Streams IVS Intrusion, Tripwire, Accurate Human/Vehicle Classification, SMD Plus Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p>		64,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
27	IPC-HFW2531TP-AS-S2	<p>5MP Lite IR Fixed-focal Bullet Network Camera 5MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.6 high image definition 5MP@20fps, 3.6mm fixed Lens SMART H.264+/H.265+, IVS Intrusion/Tripwire 1ch Alarm I/O, 1ch Audio I/O, Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, IR LED 80m Distance, Onvif Profile S/G/T</p>		39,500,000
				
28	HFW2431SP-S-S2	<p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 x 1520)@20 fps,2560 x 1440 @25fps Min. illumination:0.008 Lux@F1.6, 3.6mm Fixed lens WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance: 30 m, Smart IR, IP67, PoE</p>		25,500,000
				
29	HFW2231SP-S-S2	<p>2MP WDR IR Bullet Network Camera, starlight 1/2.8" 2Megapixel progressive CMOS Min. illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 x 1080) @25/30 fps, 3.6mm Fixed lens SMART H.264/H.265 dual-stream encoding, IVS(Tripwire, intrusion) WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>		23,600,000
				
30	HFW2230SP-S	<p>2MP IR Bullet Network Camera 1/2.7" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 3.6mm, Max. IR LEDs Length 30m, Smart IR Micro SD card memory 128 GB, IP67, PoE, AVI(Tripwire Intrusion)</p>		21,900,000
				
31	IPC-HFW2231T-ZS-S2	<p>2MP Lite IR Vari-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS, low illuminance 0.002 Lux@F1.5 high image definition 2MP@25/30fps, 2.7-13.5mm Motorized Lens, SMART H.264+/H.265+ IVS Intrusion, Tripwire, Micro SD card 256 GB WDR(120db), ROI, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, IK10, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p>		46,500,000
				
32	DH-IPC-HFW1239S1-LED-S5	<p>2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens SMART H.264+/H.265+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance, Onvif Profile S/T</p>		17,700,000
				
33	HFW1230SP-S4-S5	<p>2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 x 1080p) @25/30 fps Min. illumination:0.01 Lux@F2.0 3.6 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR IP67, PoE</p>		17,500,000
				
34	HDBW5831EP-ZE	<p>1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840x2160),25/30fps@3M(2304x1296) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 12mm motorized lens 1/1 Audio in/Out, 1/1 Alarm In/Out Micro SD card memory , 128 GB Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE+, (Tripwire Intrusion Object Abandoned/Missing Face)</p>		88,000,000
	 			
35	HDBW5431EP-Z-H	<p>1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 &amp; MJPEG triple-stream encoding Max 20fps@4Mp(2560x1440),25/30fps@3M(2304x1296) WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens, Max. IR LEDs Length 50m IP67,IK10, PoE, Micro SD card memory , 128 GB Audio in/Out, Alarm In/Out Smart Detection (Tripwire Intrusion   Scene Change   Face)</p>		75,000,000
				
36	HDBW4831EP-ASE	<p>1/2.5" 4K progressive scan Starvis CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840x2160),25/30fps@3Mp(2304x1296) WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens, Max. IR LEDs Length 30m Alarm in/out, Audio in/out Micro SD card memory , 128 GB, IP67,IK10, PoE Smart Detection (Tripwire Intrusion Scene Change Object Abandoned/Missing  Face)</p>		53,000,000
				


ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
37	HDW4831EMP-ASE 	1/2.5" 4K progressive scan CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840x2160),25/30fps@3Mp(2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens, Max. IR LEDs Length 50m Built-in Mic , Micro SD card memory , 128 GB IP67,PoE, (Tripwire Intrusion Scene Change Object Abandoned/Missing  Face)		53,000,000
38	HDW4631EM-ASE <b>Eco-Savvy Lite</b> 	1/2.9" 6Megapixel progressive scan STARVISTM CMOS H.265+ & H.265 & H.264+ & H.264 triple-stream encoding 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens, Built-in Mic Max. IR LEDs Length 50m, Smart IR Micro SD card memory , 128 GB, IP67, PoE (Tripwire Intrusion  Object Abandoned/Missing  Face)		44,000,000
39	HDW4431EMP-AS-S4	4MP IR Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688x1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE		32,200,000
	HDW3441TMP-AS-0280B 	4MP IR Fixed focal Eyeball WizSense Network Camera 1/3"4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.6 2.8mm Motorized lens 25/30fps@4Mp(2688x1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Rol Built-in Mic Micro SD memory 256GB		34,000,000
40	HDBW2531RP-ZAS 	1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@5M(2592x1944)&25/30fps@3M(2304x1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Micro SD card 128GB Max IR LEDs Length 30m ,Smart IR IP67,IK10, PoE		52,500,000
41	IPC-HDBW2531E-S-S2 	<b>NEW</b> 5MP Lite IR Fixed-focal Dome Network Camera 5MP, 1/2.7" Progressive CMOS Min. Illumination 0.008 Lux @ F1.6 Max 5MP@20fps SMART H.264+/H.265+ IVS: Intrusion, tripwire Micro SD card 256GB WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Rol max IR distance: 30m, 12V DC, PoE, IP67,IK10		28,000,000
42	IPC-HDW2439TP-AS-LED 	<b>NEW</b> 4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 2.8mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T		28,200,000
43	HDBW2431RP-ZAS-S2 	4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 x 1520)@20 fps,2560 x 1440 @ 25fps Min. Illumination:0.008 Lux@F1.5 2.7~13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, Built in Mic 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE		49,200,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
44	HDBW2431EP-S-S2	<p>4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 2.8mm/3.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE</p>		25,500,000
45	HDW2431TMP-AS-S2	<p>4MP WDR IR Eyeball Network Camera, Starlight 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6 2.8 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, Built in Mic max IR distance:30 m, Smart IR IP67, PoE</p>		26,800,000
46	HDW1431T1P-0280B-S4-S5	<p>4MP Entry IR Fixed-focal Eyeball Network Camera 1/3"4Megapixel progressive CMOS 20fps@4.1M(2688×1520) &amp; 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI Max. IR LEDs Length 30m, IP67, PoE</p>		21,000,000
47	HDW2231TMP-AS-S2	<p>2MP WDR IR Eyeball Network Camera, Starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>		24,300,000
48	IPC-HDW2231TP-AS-S2	<p><b>NEW</b> 2MP Lite IR Fixed-focal Eyeball Network Starlight Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.002 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Roi, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T</p>		23,600,000
49	IPC-HDW2230T-AS-S2	<p><b>NEW</b> 2MP IR Eyeball Network Camera 2MP, 1/2.7" Progressive CMOS low illuminance 0.005 Lux @ F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion, Tripwire Micro SD 256GB, Built-in Mic DWDR, 3D DNR, HLC, BLC, AWB, AGC, Roi, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T</p>		21,900,000
50	DH-IPC-HDW1239T1-LED-S5	<p><b>NEW</b> 2MP Lite Full-color Fixed-focal Eyeball Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T</p>		17,700,000
51	HDW1230T1P-S4	<p>2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 2.8 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS max IR distance:30 m, Smart IR IP67, PoE</p>		16,300,000
52	HDBW1230EP-S4-S5	<p>1/2.7" 2Megapixel progressive scan CMOS, 3.6mm fixed lens H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE</p>		18,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
53	DH-SD29204T-GN	<p>1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical Zoom H.264+/H.264 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 100°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion   Scene Change   Face   Abandoned-Missing Object)</p>		49,700,000
54	DH-SD1A203T-GN	<p>1/2.8" 2MP STARVIS™ CMOS (Starlight) H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 25/30fps@1080P, 2.7mm ~ 8.1mm , 3x Optical Zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max Pan: 80° /s; Tilt: 40° /s speed Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE (Tripwire Intrusion Abandoned/Missing Face Detection)</p>		53,000,000
55	DH-SD6CE230U-HNI	<p>1/2.8" 2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P 4.5mm~135mm Powerful 30x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map), Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 7/2 in/out, Audio 1/1 in/out, 1*Video output RS485, IR Distance up to 200m, PoE+, IP67, IK10</p>		237,000,000
56	SD6CE225U-HNI	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P, 4.8mm~120mm 25x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC Support Defog, ROI, EIS, Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 Alarm 7/2 in/out, Audio 1/1 in/out IR Distance up to 200m, PoE+, IP67, IK10</p>		158,000,000
57	DH-SD6CE245U-HNI	<p>2MP 45x Starlight IR PTZ Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWB Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10</p>		Call
58	SD49225XA-HNR	<p>2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P,960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>		138,000,000
59	SD49225T-HN-S2	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6)B/W:(0.0005Lux@F1.6) Max. 25/30fps@1080P, 4.8mm~120mm 25x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR,BLC, HLC, AWB, AGC, ROI Support Defog IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 2/1 Alarm in/out, 1/1 Audio in/out Support PoE+, IR Distance up to 100m, IP66</p>		128,000,000












رقم	نموذج	مواصفات فنية	تصوير	قيمة (ريال)
60	SD56F230F-HNI	<p>1/1.9" 2MP CMOS Sensor(Super Starlight)  H.264 / MJPEG Encoding  Max. 25/30fps@1080P, 25/30/50/60fps@720P  6mm~180mm Powerful 30x optical zoom  Max 300°/s pan speed, 360° endless pan rotation  WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC, Auto iris, Auto focus  Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection)  Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan  Support Defog, ROI, EIS  Alarm 7/2 in/out, Audio 1/1 in/out, 1 video output  RS485, IR Distance up to 100m, Support PoE+, IP66, IK10</p>		Call
				
61	DH-SD59432XA-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera  1/2.8" STARVIS™ CMOS  H.265+/H.265/H.264+/H.264 Encoding  Min. Illumination: Color(0.005Lux@F1.3)B/W(0.0005Lux@F1.3)  Max. 25/30fps@4M  4.9 mm~156 mm Focal Length, 32x optical zoom  <b>Deep-learning-based auto tracking and perimeter protection(Recognition of human and vehicle)</b>  IVS(Tripwire, intrusion, Object abandoned/missing, Face Detection)  WDR(120dB), Day/Night(ICR), Ultra DNR, AWB, AGC, BLC, HLC  Support Defog and EIS , Roi  Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan  2/1 Alarm in/out, Audio 1/1 in/out  Support PoE+, IR Distance up to 150m, IP66</p>		295,000,000
				
62	SD59225U-HNI	<p>2MP 25x Starlight IR PTZ Network Camera  1/2.8" Exmor R CMOS  H.265+/H.265/H.264+/H.264 Encoding  Max. 50/60fps@1080P, 25/30/50/60fps@720P  4.8mm~120mm 25x optical zoom  Max 400°/s pan speed, 360° endless pan rotation  WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus  Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection), Support Defog and EIS  Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan  Built-in 2/1 Alarm in/out, Audio 1/1 in/out  Support PoE+, IR Distance up to 150m, IP66, OSD</p>		148,000,000
				
63	SD59230U-HNI	<p>2MP 30x Starlight IR PTZ Network Camera  1/2.8" Exmor R CMOS  H.265+/H.265/H.264+/H.264 Encoding  Max. 50/60fps@1080P, 25/30/50/60fps@720P  4.5mm~135mm 30x optical zoom  Max 400°/s pan speed, 360° endless pan rotation  WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus  Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection), Support Defog and EIS  Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan  Built-in 2/1 Alarm in/out, Audio 1/1 in/out  Support PoE+, IR Distance up to 150m, IP66, OSD</p>		220,000,000
				
64	SD59430U-HNI	<p>1/3" CMOS Sensor  H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rate  Max. 25/30fps@4M(2592x1520) &amp; 50/60fps @1080P resolution  WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus  4.5mm ~ 135.0mm , 30x Optical Zoom  Max 400°/s pan speed, 360° endless pan rotation  Up to 300 presets, 5 auto scan, 8 tour, 5 pattern  Micro SD card memory , 64 GB  Audio In/Out, Alarm In/Out, IP66, POE+  IR Distance up to 100m(AC24V)/ 80m(DC12V)  Smart Detection (Tripwire Intrusion   Scene Change   Face   Anandoned-Missing Object)</p>		248,000,000
		<b>NEW</b>		
65	SD5A432XA-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera  1/2.8" 4Megapixel STARVIS™ Progressive CMOS  H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M  Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.35, 0 Lux (IR on)  4.9 mm~156 mm Powerful 32x optical zoom, Max. Aperture F1.35~F4.4  Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°~360° endless rotation  WDR(120), EIS, Defog, Roi, 2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR  Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor  vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering  Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan  Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&amp;G&amp;T  IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection; voltage transient  protection</p>		280,000,000
				



مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
66	<p><b>NEW</b></p> <p>4MP 45x Starlight IR WizSense Network PTZ Camera                      1/2.8" 4Megapixel STARVIS™ Progressive CMOS                      H.265/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max. 25/30fps@4M                      Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux (IR light on)                      3.95 mm~177.7 mm Powerful 45x optical zoom Max. Aperture F1.6~F4.95                      Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°~360° endless rotation                      WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR                      Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor                      vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering                      Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan                      Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&amp;G&amp;T                      IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection</p>		330,000,000
67	<p>1/2.8" 2Mp CMOS Sensor                      H.264+/H.264 Encoding, Ultra-low bit rate transmission                      Max. 30fps@1080P(2592x1520) &amp; 60fps @720P resolution                      DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus                      4.5mm ~ 135.0mm , 30x Optical Zoom                      Max 600°/s pan speed, 360° endless pan rotation                      Up to 300 presets, 5 auto scan, 8 tour, 5 pattern                      Micro SD card memory , 64 GB                      Audio In/Out, Alarm In/Out                      IP67,IK10, POE+, (Tripwire)Intrusion   Scene Change   Face   Anononed-Missing Object)</p>		Call
68	<p><b>NEW</b></p> <p>4 Channel IPC Input, 4K Lite H.265 NVR 1/4 Live &amp; Playback                      Smart H.265+/Smart H.264+/H.265/H.264                      Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding.                      Up to 8MP Resolution for Preview &amp; Playback                      Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or                      2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS)                      Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P                      1 SATA 2.0 port, up to 8TB                      1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only                      1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>		19,200,000
69	<p>4 channel IP camera input                      H.265/H.264 codec decoding                      Max 80Mbps incoming bandwidth                      Up to 8Mp resolution preview&amp;playback                      Up to 1ch@8MP/4ch@1080P decoding                      HDMI/VGA simultaneous video output                      Support 1 SATA HDD up to 6TB, 2 USB2.0                      100 Mbps Network Card, P2P support</p>		21,700,000
70	<p>4 channel IP camera input, H.265/H.264 codec decoding                      Max 80Mbps incoming bandwidth                      Up to 8Mp resolution preview&amp;playback                      Up to 1ch@8MP/4ch@1080P decoding                      HDMI/VGA simultaneous video output                      Support 1 SATA HDD up to 6TB, 2 USB2.0                      100 Mbps Network Card, 4PoE Port, P2P support</p>		29,000,000
71	<p><b>NEW</b></p> <p>8 Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live &amp; Playback                      Smart H.265+/Smart H.264+/H.265/H.264                      Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding.                      Up to 8MP Resolution for Preview &amp; Playback                      Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or                      2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS)                      Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P                      1 SATA 2.0 port, up to 8TB                      1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only                      1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)                      8 channel IP camera input, H.265/H.264 codec decoding                      Max 80Mbps incoming bandwidth                      Up to 8Mp resolution preview&amp;playback                      Up to 1ch@8MP/4ch@1080P decoding                      HDMI/VGA simultaneous video output                      Support 1 SATA HDD up to 6TB, 2 USB2.0                      100 Mbps Network Card, P2P support</p>		21,800,000
72	<p>8 channel IP camera input, H.265/H.264 codec decoding                      Max 80Mbps incoming bandwidth                      Up to 8Mp resolution preview&amp;playback                      Up to 1ch@8MP/4ch@1080P decoding                      HDMI/VGA simultaneous video output                      Support 1 SATA HDD up to 6TB, 2 USB2.0                      100 Mbps Network Card, P2P support</p>		24,000,000
73	<p>8 channel IP camera input, H.265/H.264 codec decoding                      Max 80Mbps incoming bandwidth                      Up to 8Mp resolution preview&amp;playback                      Up to 1ch@8MP/4ch@1080P decoding                      HDMI/VGA simultaneous video output                      Support 1 SATA HDD up to 6TB, 2 USB2.0                      100 Mbps Network Card, 8Port PoE, P2P support</p>		39,000,000
74	<p><b>NEW</b></p> <p>8 Channel 12MP WizSense NVR 1/4/8 Live &amp; Playback                      Smart H.265+/H.264+/MJPEG                      Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding                      Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps                      Ai Enabled : 1ch 8MP@30fps or 1ch 5MP@30fps or 2ch 4MP@30fps or 4ch 2MP@30fps                      HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p                      1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library                      or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification                      1 SATA II port, up to 8TB                      1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port                      1 RJ-45 port (100Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		32,800,000



ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
75	NVR4108HS-4KS2	<p>8 channel IP camera input 1/4/8/9 channel Live Preview, 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		28,000,000
76	DHI-NVR2216-4KS2	<p>16 Channel 4K Lite H.265 NVR 1/4 Live &amp; Playback Dual-core embedded processor, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output 2 SATA III Ports, up to 6TB capacity for each, Total 12TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support 16 Channel 12MP WizSense NVR 1/4/9/16 Live &amp; Playback</p>		40,000,000
77	NVR2116HS-I	<p>Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G) 16 Channel 12MP WizSense NVR 1/4/9/16 Live &amp; Playback</p>		39,000,000
78	DHI-NVR2216-I	<p>Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 2 SATA 2.0 port, up to 8TB each, Total 16TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G) 16 channel IP camera input, 16 channel Live Preview</p>		55,000,000
79	NVR4116HS-4KS2/L	<p>Smart H.265+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback 16-ch@720P decoding capacity Support SMD Plus by Camera HDMI(4K)/VGA simultaneous video output Support 1 SATA HDD up to 8TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		41,000,000
80	NVR4216-4KS2/L	<p>16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)</p>		52,000,000
81	NVR4232-4KS2	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*1000Mbps Network Card, P2P support</p>		62,500,000
82	DHI-NVR5232-4KS2(V2.0)	<p>32Channel 1U 4K &amp; H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 1*HDMI(4K)/1*VGA simultaneous video output 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0) 1*1000 Mbps Network Card, RS232, RS485,4/2 Alarm In/out , P2P Support</p>		108,000,000
83	NVR4432-4KS2	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding, Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 4 SATA HDD up to 6TB, 2 USB Ports (1 USB2 &amp; 1 USB3) 16 Alarm Input, 4 Relay Output, RS232, RS485 2*10/100/1000Mbps Mbps Network Card, P2P support 32Channel 1.5U 4K &amp; H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth</p>		89,000,000
84	NVR5432-4KS2(V2.0)	<p>Up to 12Mp resolution preview &amp; playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out, P2P Support</p>		149,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
85	DHI-NVR5464-4KS2(V2.0)	<p>64Channel 1.5U 4K&amp;H.265 Pro Network Video Recorder (V2.00)  Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding  Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback  Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding  2*HDMI/2*VGA simultaneous video output  4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0)  Support 1 e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Suooort  32 channel IP camera input, 16 channel Live Preview  H.265/H.264 codec decoding</p>		175,000,000
86	NVR4832-4KS2	<p>Max 200Mbps incoming bandwidth, Up to 8MP Resolution for Preview and Playback  HDMI/VGA simultaneous video output  Support 8 SATA HDD up to 6TB, 3 USB Ports (2 USB2.0, 1 USB3.0)  16 Alarm Input, 4 Relay Output, RS232 , RS485  2*10/100/1000Mbps Mbps Network Card, P2P support  32 channel IPC input, 32 Channel Live Preview  H.265/H.264/MJPEG/MPEG4 codec decoding</p>		143,000,000
87	NVR5832-4KS2	<p>Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview&amp;playback  Max 16ch@1080P   4ch@4K H.265   H.264 Playback  2HDMI/VGA simultaneous video output  Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0)  2*1000 Mbps Network Card, RS232, 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10  64 Channel 2U 4K &amp; H.265 Pro Network Video Recorder (V2.00)  Smart H.265+/H.265/H.264+/H.264/MJPEG decoding</p>		210,000,000
88	DHI-NVR5864-4KS2(V2.0)	<p>Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback  Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding  2*HDMI/2*VGA simultaneous video output  8*SATA HDDs(10 TB for each HDD), 4 USB(2 USB3.0,2 USB2.0)  1*e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support  Intel Dual-core Processor, 32 channel IPC input, 32 Channel Live Preview  (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16)  H.265/H.264/MJPEG codec decoding, Max 384Mbps incoming bandwidth</p>		265,000,000
89	NVR608-32-4KS2	<p>Up to 12Mp resolution preview&amp;playback  2HDMI/VGA simultaneous video output  Support 8 SATA HDDs up to 48TB,1 eSATA Port  Support Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0)  2*1000 Mbps Network Card, RS232 , RS485, 16 Alarm In , 8 Relay Output  Intel Quad-core Processor  64 channel IPC input, 32 Channel Live Preview  (1st Screen:1st Screen: 1/4/8/9/16/25/36, 2nd Screen: 1/4/8/9/16), H.265/H.264/MJPEG codec decoding</p>		225,000,000
90	NVR608-64-4KS2	<p>Up to 12Mp resolution preview &amp; playback  2HDMI/VGA simultaneous video output  Support 8 SATA HDDs up to 48TB,1 eSATA Port  Support Raid 0/1/5/6/10  Support Smart Tracking and Intelligent Video  4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card  RS232 , RS485, 16 Alarm In , 8 Relay Outout  128 Channel 2U Ultra 4K H.265 Network Video Recorder  (1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16)  H.265/H.264/MJPEG codec decoding  Max 384Mbps incoming bandwidth</p>		380,000,000
91	DHI-NVR608-128-4KS2	<p>Up to 12Mp resolution preview &amp; playback  2HDMI(different Source)/VGA simultaneous video output  Support 8 SATA (8TB for each HDD),1 eSATA Port  Support Raid 0/1/5/10  Support Smart Tracking and Intelligent Video  4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card  RS232 , RS485, 16/6 Alarm in/Output  2U standard 19-inch rack case  Connect master device via eSATA or USB  1 eSATA port transmission speed up to 3Gbps  1 USB 3.0 port data transmission higher than normal  Powerful R / W performance: read &gt;64MB/s, write &gt;64MB/s  ESS1508C: Max support Internal 8 SATA HDD up to 48TB  Recommended with DVR, NVR connection  4-Port Fast Ethernet PoE Switch, Layer two commercial switch  2*10/100 Mbps Uplink ports, 4*10/100 Mbps PoE ports  Port1≤60W, Port2-4≤30W, Totals≤60W</p>		470,000,000
92	ESS1508C	<p>Support IEEE802.3af, IEEE802.3at(PoE+) ,Hi PoE  1.8Gbps Switching Capacity  890Kpps Mpps Packet Forwarding Rate  768Kb Packet Buffer Memory  MAC Table size is 7K, Supports DC 48-57V power supply  8-Port Fast Ethernet PoE Switch, Layer two commercial switch  2*10/100/1000 Mbps Ports, 8*10/100 Mbps PoE Ports  Port1≤60W, Port2-8≤30W, Totals≤96W</p>		78,000,000
93	PFS3006-4ET-60	<p>Support IEEE802.3af, IEEE802.3at(PoE+) ,Hi PoE  1.8Gbps Switching Capacity  890Kpps Mpps Packet Forwarding Rate  768Kb Packet Buffer Memory  MAC Table size is 7K, Supports DC 48-57V power supply  8-Port Fast Ethernet PoE Switch, Layer two commercial switch  2*10/100/1000 Mbps Ports, 8*10/100 Mbps PoE Ports  Port1≤60W, Port2-8≤30W, Totals≤96W</p>		11,700,000
94	PFS3010-8ET-96	<p>Support IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE  5.6Gbps Switching Capacity, 4.17 MppsPacket Forwarding Rate  4Mb Packet Buffer Memory  MAC Table Size is 16K, Supports DC 48-57V power supply  Two-layer industrial PoE switch  1*1000 Base-X, 1*10/100/1000 Base-T  8*10/100 Base-T (PoE power supply)  Each POE power ≤30W, Totals≤96W</p>		21,400,000
95	PFS3110-8P-96	<p>Support IEEE802.3af, IEEE802.3at standard  7.6G Switching Capacity, 4.17 MppsPacket Forwarding Rate  1Mb Packet Buffer Memory, Industrial wide temperature design  MAC auto studv and aging, MAC address list capacity is 8K</p>		26,700,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
96	PFS4218-16ET-190	<p>Layer 2 management PoE switch            2*10/100/1000 Base-T (Combo port)            2*1000 Base-X (Combo port)            16*10/100 Base-T (PoE power supply)            Port1/2 support Hi-PoE (60W), PoE+, PoE            Each power ≤30W, Totals≤190W            Support IEEE802.3af, IEEE802.3at, Hi-PoE            250 meters long distance PoE transmission            Support spanning tree protocol STP/RSTP            Support Vlan:VLAN/802.1Q Standard Vlan            8.8G Switching Capacity,5.36 Mpps Packet Forwarding Rate            Network Management by WFR(http and https protocol)            Layer 2 management PoE switch</p>		67,500,000
97	PFS4218-16ET-240	<p>2*10/100/1000 Base-T (Combo port)            2*1000 Base-X (Combo port)            16*10/100 Base-T (PoE power supply)            Port1/2 support Hi-PoE (60W), PoE+, PoE            Each power ≤30W, Totals≤240W            Support IEEE802.3af, IEEE802.3at, Hi-PoE            250 meters long distance PoE transmission            Support spanning tree protocol STP/RSTP            Support Vlan:VLAN/802.1Q Standard Vlan            8.8G Switching Capacity, 5.36 Mpps Packet Forwarding Rate            Network Management by WFR(http and https protocol)</p>		73,000,000
98	PFS4226-24ET-240	<p>24-Port PoE Switch, Layer 2 management PoE switch            2*10/100/1000 Base-T (Combo port), 2*1000 Base-X (Combo port)            24*10/100 Base-T (PoE power supply)            Port1/2 support Hi-PoE (60W), PoE+, PoE            Each power ≤30W, Totals≤240W, Support IEEE802.3af, IEEE802.3at, Hi-PoE            250 meters long distance PoE transmission            Support spanning tree protocol STP/RSTP, Support Vlan:VLAN/802.1Q Standard Vlan            8.8G Switching Capacity, 6.55 Mpps Packet Forwarding Rate            Network Management by WEB(http and https protocol)            24-Port PoE Switch, Layer 2 management PoE switch</p>		80,600,000
99	PFS4226-24ET-360	<p>2*10/100/1000 Base-T (Combo port)            2*1000 Base-X (Combo port)            24*10/100 Base-T (PoE power supply)            Port1/2 support Hi-PoE (60W), PoE+, PoE            Each power ≤30W, Totals≤360W, Support PoE, PoE+, Hi-PoE            'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300)            250 meters long distance PoE transmission            Support spanning tree protocol STP/RSTP            Support Vlan:VLAN/802.1Q Standard Vlan            8.8G Switching Capacity, 6.55 Mpps Packet Forwarding Rate            Support Web management, Non-blocking video transmission            management PoE Setting/Event Statistics/Green PoE            24-Port PoE Gigabit Managed Switch            Layer 2 network management PoE switch</p>		96,700,000
100	PFS4226-24GT-360	<p>24*10/100/1000 Base-T (PoE power supply)            2*100/1000 Base-X, Port1/2 support Hi-PoE (60W)            Each power ≤30W, PoE Budgets≤360W            Spanning tree: STP/RSTP/MSTP            Network management based on SNMP            Configuration: Web, Telnet, CLI Command            Support Vlan:VLAN/802.1Q Standard Vlan, 8K MAC Table            52G Switching Capacity, 38.688 Mpps Packet Forwarding Rate            EMC high protection design</p>		123,000,000
101	PFT1300	<p>PoE Extender            1*10/100 Base-T PoE power receiving port            1*10/100 Base-T PoE power supply port, supply power for the next extender            1*10/100 Base-T PoE power supply port, supply power for IPC            Support passive PoE cascade power supply and Ethernet data exchange            Support IEEE 802.3af/at standard power supply IP Camera            able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption ≤8W), max transmission distance 300m</p>		5,150,000
102	PFM700	<p>*1 Channel HDMI Transmission Signal            *1080P/1080i/720P/576P/576i/480P/480i Resolution Output Signal , *60M (max)Transmission Distance            *Input voltage DC5V            *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video, signal:support HDMI 1.3</p>		14,400,000
103	NKB1000	<p>Keyboard to Control : Dahua High Speed Dome (all models)            Dahua Standalone DVR , Dahua Network High Speed Dome            Network Video Server            Connection : RS485, RS422, USB, RS232 &amp; Network            Three Dimensional Joystick Control of PTZ Functions            Preset Position, Auto Scan, Auto Pan, Auto Tour &amp; Pattern Control, On-Screen Menu &amp; User Operation Procedure Tips            Connect to SmartPSS via USB</p>		78,000,000